



TYPICAL PROPERTIES

Kinematic Viscosity, @ 100°C	13.3 cSt
Kinematic Viscosity, @ 40°C	82.3 cSt
Viscosity Index	164
Cold Crank Simulator, @ -35°C	5,470cP
Pour Point	-42°C
Flash Point, COC	>200°C
Density, @ 15°C	0.847 g/cm ³

Values are typical of current production, and whilst future production will meet these specifications, some variation in typical data may occur.
Version Date: 19/02/2025

HyperDrive KXR 5W-40 C3

CODE: KXEER41

HyperDrive KXR 5W-40 C3 is a high performance fully synthetic mid SAPS long life engine oil, designed for use in passenger car petrol and diesel engines, including direct injection engines, fitted with exhaust after treatment systems which require an ACEA C3 5W-40 oil meeting the specifications below. Expertly formulated to ensure adequate film thickness at operating temperatures, including low temperature start-ups, to protect against wear and corrosion. The oil reduces internal friction to improve engine efficiency and reduce emissions. Top tier additives ensure the oil protects throughout the recommended oil drain interval whilst still protecting exhaust after treatment systems.

FEATURES / BENEFITS

- Fully synthetic engine oil designed to protect engines from wear, and corrosion, even at low temperature start-ups, whilst reducing internal friction, improving engine efficiency and reducing fuel consumption and environmental emissions
- Mid SAPS formulation protects exhaust after treatment systems, such as particulate filters and three-way catalysts (TWC), further reducing environmental emissions
- High quality base oils and top tier additives ensure that the oil is shear stable and remains within grade for the oil ensuring adequate protection of the engine throughout the recommended oil drain interval
- Excellent oxidation stability protects the oil throughout extended oil drain intervals, reducing the build-up of sludges and deposits within the oil and the engine, maintaining engine condition and performance
- Suitable for use in high performance passenger car petrol and diesel engines, including direct injection engines, fitted with exhaust after treatment systems which require an ACEA C3 5W-40 oil meeting the specifications below

PERFORMANCE SPECIFICATIONS

HyperDrive KXR 5W-40 C3 meets the requirement of:

- ACEA: C3
- API: SN
- BMW: LL-04
- GM: Dexos 2
- MB: 229.51
- PORSCHE: C40
- VW: 502 00 / 505 01

AVAILABILITY



Certas Energy UK Ltd., T/A Certas Lubricants Solutions. 1st Floor, Allday House, Warrington Road, Birchwood, Warrington, Cheshire, WA3 6GR.
Tel: 0800 371 910 hyperdrivelubricants.com