



## HyperDrive KX+

# HM Hydraulic Fluids

CODE: KXEHAxx

HyperDrive KX+ HM Hydraulic Fluids are premium quality hydraulic fluid, formulated from high viscosity index solvent refined mineral oil with zinc based anti-wear additives. Protects against wear, corrosion and oxidation to maintain equipment condition throughout the oil drain interval.

## FEATURES / BENEFITS

- Anti-wear additives minimises wear and extends equipment life
- Corrosion protection protects equipment throughout oil drain interval
- Excellent extreme pressure performance protects equipment from high pressures and shock loading
- Excellent oxidation stability maintains oil condition and cleanliness throughout oil drain interval

## PERFORMANCE SPECIFICATIONS

HyperDrive KX+HM Hydraulic fluid meets the requirements of:

- ASTM: D6158 Type HM • AFNOR NFE 48-603 HM
- DIN: 51 524 Part 2 (HLP) • EATON (VICKERS): I-286-S • ISO: ISO 11158 Category HM • US STEEL 126 & 127

## AVAILABILITY



## TYPICAL PROPERTIES

Type	ISO 32	ISO 46	ISO 68
Code	EHA15	EHA20	EHA17
Kinematic Viscosity, @ 40°C	32.0 cSt	46.0 cSt	68.0 cSt
Kinematic Viscosity, @ 100°C	5.2 cSt	6.8 cSt	8.9 cSt
Viscosity Index	99	100	104
Flash Point, COC	>210 °C	>230 °C	>240 °C
Pour Point	-30 °C	-27 °C	-18 °C
Density, @ 15°C	0.873 g/cm <sup>3</sup>	0.876 g/cm <sup>3</sup>	0.880 g/cm <sup>3</sup>

Values are typical of current production, and whilst future production will meet these specifications, some variation in typical data may occur.  
Version Date: 17/12/2024

Certas Energy UK Ltd., T/A Certas Lubricants Solutions. 1st Floor, Allday House, Warrington Road, Birchwood, Warrington, Cheshire, WA3 6GR.  
Tel: 0800 371 910 [hyperdrivelubricants.com](http://hyperdrivelubricants.com)