



## HyperDrive KX+

# TTF - Tractor Transmission Fluid

CODE: KXEMA10

HyperDrive KX+ TTF Tractor Transmission Fluid is a premium Universal Tractor Transmission Oil (UTTO) for use in tractors, agricultural machines and off-highway vehicles where either an SAE 80W or 10W-30 oil is required for transmission and hydraulic applications. Formulated with high quality base oils and premium multi-functional additives, this one oil can protect transmission, final drive, and hydraulic systems including wet brakes. Suitable for year-round use, this product protects equipment whilst reducing inventory and complexity.

## FEATURES / BENEFITS

- Universal Tractor Transmission Oil (UTTO), suitable for agricultural and off-highway vehicles where a single SAE 80W or 10W-30 oil can be used for transmission, final drive and hydraulic systems, reducing inventory and minimising the risk of incorrect lubricant application
- Not suitable for lubricating engines, please consider HyperDrive KX+ SUTO - Super Universal Tractor Oil
- Formulated with high quality base oil, this multigrade oil is suitable for use across a wide temperature range, ensuring protection at both low temperature start-up and during high temperature operations
- Premium additive package gives wear and frictional control, maintaining manual transmission gearboxes and final drive condition, reducing downtime, and extending component life
- Good hydraulic performance protects pumps and other components from wear and corrosion, maintaining performance and ensuring consistent, smooth operations of hydraulic systems

## PERFORMANCE SPECIFICATIONS

HyperDrive KX+ TTF Tractor Transmission Fluid meets the requirements of:

- API: GL-4
- ALLISON: C-4
- JOHN DEERE: J20D / J20C
- MASSEY FERGUSON: M1145
- SPERRY VICKERS: M2950S, I-280-S
- VOLVO: WB101
- ZF: TE-ML 06H, TE-ML 06F

HyperDrive KX+ TTF Tractor Transmission Fluid is suitable for use where the following specification are required:

- CASE INTERNATIONAL: MS-1209, MS-1207, MS-1206, MS-1204
- CATERPILLAR: TO-2
- FORD: M2C-86C, M2C-86B, M2C-134D
- MASSEY FERGUSON: M1143, M1141, M1135

## AVAILABILITY



## TYPICAL PROPERTIES

Kinematic Viscosity, @ 100°C	10.9 cSt
Kinematic Viscosity, @ 40°C	69.4 cSt
Viscosity Index	149
Cold Crank Simulator, @ -25°C	4,200cP
Pour Point	-42°C
Flash Point, COC	>228°C
Density, @ 15°C	0.877 g/cm <sup>3</sup>

Values are typical of current production, and whilst future production will meet these specifications, some variation in typical data may occur.  
Version Date: 02/04/2025

Certas Energy UK Ltd., T/A Certas Lubricants Solutions. 1st Floor, Allday House, Warrington Road, Birchwood, Warrington, Cheshire, WA3 6GR.  
Tel: 0800 371 910 [hyperdrivelubricants.com](http://hyperdrivelubricants.com)