

HYPERDRIVE



TYPICAL PROPERTIES

Kinematic Viscosity, @ 100°C	11.7 cSt
Kinematic Viscosity, @ 40°C	66.5 cSt
Viscosity Index	173
Cold Crank Simulator, @ -30°C	5,960cP
Pour Point	-45°C
Flash Point, COC	>240°C
Density, @ 15°C	0.850 g/cm ³

HyperDrive KXR 5W-30 C3 VAG

CODE: KXEEH40

HyperDrive KXR 5W-30 C3 VAG is a high performance fully synthetic mid SAPS long life engine oil, designed for use in in passenger car petrol and diesel engines, fitted with exhaust after treatment systems which require an ACEA C3 5W-30 oil meeting the specifications below. Expertly formulated to ensure adequate film thickness at operating temperatures, to protect against wear and corrosion. The low viscosity oil reduces internal friction to improve engine efficiency and reduce emissions. Top tier additives ensure the oil protects throughout the recommended oil drain interval whilst still protecting exhaust after treatment systems.

FEATURES / BENEFITS

- Fully synthetic low viscosity engine oil designed to protect engines from wear, and corrosion, whilst reducing internal friction, increasing engine efficiency and reducing fuel consumption and environmental emissions
- Mid SAPS formulation protects exhaust after treatment systems, such as particulate filters and three-way catalysts (TWC), further reducing environmental emissions
- High quality base oils and top tier additives ensure that the oil is shear stable and remains within grade for the oil ensuring adequate protection to the engine throughout the recommended oil drain interval
- Excellent oxidation stability protects the oil throughout extended oil drain intervals, reducing the build-up of sludges and deposits within the oil and the engine, maintaining engine condition and performance.
- Suitable for use in high performance passenger car petrol and diesel engines, with or without exhaust after treatment systems which require an ACEA C3 5W-30 oil, especially European cars produced by BMW, Mercedes Benz and Volkswagen Audi Group

PERFORMANCE SPECIFICATIONS

HyperDrive KXR 5W-30 C3 VAG meets the requirements of:

- ACEA: C3
- API: SN
- BMW: LongLife-04
- MB: 229.5
- VW: 504 00 / 507 00

AVAILABILITY









Values are typical of current production, and whilst future production will meet these specifications, some variation in typical data may occur.

Version Date: 21/03/2025

Certas Energy UK Ltd., T/A Certas Lubricants Solutions. 1st Floor, Allday House, Warrington Road, Birchwood, Warrington, Cheshire, WA3 6GR. Tel: 0800 371 910 hyperdrivelubricants.com